

# Health and Safety Product Data Sheet

## 1. Identification of Product

### Limestone Paving

Bekstone Ltd.  
Pavestone Ltd.  
Westington Quarry  
Chipping Campden  
Gloucestershire  
GL55 6EG

Tel: 01386 848650  
Fax: 01386 849072

## 2. Composition of Ingredients

Natural Aggregated are produced from naturally occurring rock, sand and gravel deposits and consist of combinations of various minerals including quartz. The cement admixture has irritant properties prior to curing.

## 3. Hazard Identification

Cutting lime paving can create dust, if inhaled in excessive quantities over extended periods. Respirable dust can constitute a long-term hazard.

Cutting lime Paving, unless adequately controlled, can project particles at high velocity, with consequent risk of impact damage and/or injury, particularly to exposed areas of the body and eyes.

Lifting and manual handling of large quantities can cause injury, and should be handled accordingly.

## 4. First Aid Measures

First Aid treatment is as follows:

### **Eye Contact**

Immediately rinse under running water and consider medical attention.

### **Cuts / Abrasions**

Cuts / Abrasions from handling should be cleaned and treated, using the normal first-aid method. Wounds must receive prompt medical attention.

In all doubtful cases, medical advice must be obtained.

## 5. Fire Fighting Measures

Not Applicable.

## 6. Accidental Release Measures

Avoid contact with Skin

Take up product using appropriate equipment.

## 7. Handling & Storage

Avoid contact with dust.

Always follow safe lifting and manual handling procedures.

The preferred method of handling is by mechanical means. Where storage of material is necessary in public areas accessed by the public, adequate notices, signs and markings should be used.

## 8. Exposure Controls

Although not classed as dangerous these products should be handled in accordance with good industrial hygiene and safety practices. Whilst handling products, protective gloves and boots should be worn.

During cutting or similar activity, overalls/eye/face protection should be worn, use dust masks. Respiratory protective equipment to BS 2901 Type B with extraction equipment.

## 8.1 Hand Protection

Wear suitable protective gloves.

## 8.2 Skin Protection

Avoid contact with skin.

## 8.3. Eye Protection

Wear goggles to protect eye contact from flying particles when crushing, drilling, cutting or breaking bricks.

## 8.4 Masks

Wear dust masks when crushing, drilling, cutting or breaking paving.

## 8.5 Footwear

Wear footwear with protective toecaps when working with the bricks

## 9. Physical & Chemical Properties

The paving can be abrasive and the dust contains calcium silicates.

## 10. Stability & Reactivity

Not applicable.

## 11. Toxicological Information

No risk upon observation of safety instructions 6, 7 & 8 above.

## 12. Ecological Information

Have no ecological effect.

## 13. Disposal Considerations

Limestone paving may be recycled or placed in an approved landfill.

## 14. Transportation

Ensure security and safety of load at all times.

## 15. Regulatory Information

Not Applicable

## 15. Other

The information contained in this sheet is correct to the best of our knowledge at the date of issue. It is intended as a guide of safety requirements only and it is not a specification or guarantee of specific properties. We recommend customers ensure that the product is entirely suitable for their purposes.

No liability can be accepted for any loss, injury or damage resulting from its use.