





# Black Spot & Algae Remover







# **Black Spot & Algae Remover**



Date: 01/08/2021

Ready to use deep cleaning solution that works on a wide range of outdoor surfaces to keep your patio, garden path and driveway looking their best all year round.

#### **Technical Features**

- Deep cleaning
- Controls & removes organic soiling
- Algae, mould, lichen, mildew
- Spray on formula
- Helps prevent re-growth
- Easy to use
- Interior & exterior
- High performance

## Coverage

	1 LTR	5 LTR	25 LTR
Surface cleaning	N/A	50 M <sup>2</sup> /bottle	N/A
Deep stripping	N/A	25 M <sup>2</sup> /bottle	N/A
Extreme cases	N/A	15 M <sup>2</sup> /bottle	N/A



#### **Directions for use**


#### **MANUAL APPLICATION: FLOORS**



Fill a light pressure sprayer with the solution. Do not dilute.



Set the pressure between 0.5 and 1 bar. Apply an even layer to the surface.



Leave the solution to penetrate the surface. Leave for 1-5 hours depending on the level of soiling.



Keep off of surfaces, while the solution is active. Keep pets and children away.



Rinse well with plenty of water. Allow surfaces to dry before allowing traffic or applying porcelain protector.

# **Directions for use (Cont.)**

#### **MANUAL APPLICATION: STEPS**



Fill a light pressure sprayer with the solution. Do not dilute.



Set the pressure between 0.5 and 1 bar. Apply an even layer to the surface.



Leave the solution to penetrate the surface. Leave for 1-5 hours depending on the level of soiling.



Keep off of surfaces, while the solution is active. Keep pets and children away.



Rinse well with plenty of water. Allow surfaces to dry before allowing traffic or sealing applying porcelain protector.

### **FURTHER INFORMATION**

**USEFUL EQUIPMENT:** Low pressure sprayer, short haired stiff bristled brush, paint brush, rotary scrubbing machine with onboard water tank, stiff brush attachment for the machine, wet vac, buckets, sponges, absorbant towels (for spillage control), Plastic film and maskin g tape for covering and protecting surfaces not to be cleaned. Pressure washer or hose pipe for rinsing.

Ensure that any sensitive surfaces not to be cleaned are properly covered and protected before beginning. Ensure that gloves and eye protection and suitable water proof clothing are worn at all times.

Main walkways & terraces machine application. After spraying on the cleaning solution and leaving it to work in teams of two. One opperator should agitate the surface using a rotary machine and stiff brush attachment. The other opperator

should use the wet vac for immediate extraction. This will prevent any released dirty residues re-absorbing into the pavers and greatly reduce the drying time of surfaces. Use cool water only within the tank on the scrubbing machine. Do not put intensive cleaning solution through the machine as this will impair it's effectiveness.

Balustrades, steps and risers. Start on the top of the steps/balustrades and work down. Try to work in manageable areas at a time and make sure to rinse well with plenty of water after each application. Rinsing should be repeated at least 2 times after cleaning. In areas where the staining is deep repeat the process until all of the stains have gone.

