

Patio Cleaner




 **PAVESTONE**


 WATER BASED


 **CLEAN**

PATIO CLEANER
Heavy duty cleaner for removing stubborn ground in dirt and grime from stone and porcelain paving.

5LTR_e

 **PAVESTONE**

 WATER BASED

 **CLEAN**

PATIO CLEANER
Heavy duty cleaner for removing stubborn ground in dirt and grime from stone and porcelain paving.

1LTR_e

A high performance product for stripping and cleaning of vitrified glazed ceramics, porcelain, travertine, natural stone, sandstone, slate, marble, granite, terracotta, quarry, brick, concrete, external paving, terrazzo and other mineral floors & walls. On larger areas scrubber drier machines can be used.

Coverage

	1 LTR	5 LTR	25 LTR
Surface cleaning	60 M ² /bottle	300 M ² /bottle	1500 M ² /bottle
Deep stripping	30 M ² /bottle	150 M ² /bottle	750 M ² /bottle
Extreme cases	15 M ² /bottle	75 M ² /bottle	375 M ² /bottle

Technical Features

- Non hazardous
- High performance
- Fast acting
- Easy to use
- Walls & floors
- Interior & exterior use
- Deep cleaning




Directions for use


MECHANICAL APPLICATION: FLOORS



1 Dilute solution 1:1 with warm water and fill a light pressure sprayer.



2 Wet the surface with the solution and leave for 10-15 minutes. Work in manageable areas at a time.



3 Releasing water from the on board tank and scrub surfaces and grout joints to release the dirt and grime.



4 Extract the released residues. Repeat steps 2, 3 and 4 until the surface is clean.



5 Rinse well with water. Allow surfaces to dry before allowing traffic or sealing.

Directions for use (Cont.)

MANUAL APPLICATION: FLOORS



1 Dilute solution 1:1 with cool water. Mask and protect areas not to be cleaned.




2 Wet the surface with the solution and leave for 10-15 minutes. Work in manageable areas at a time.



3 Add a little water and gently scrub surfaces with a black pad to release the loosened matter from the surface.



4 Sponge up and extract released residues. Repeat steps 2, 3 and 4 until the surface is clean.



5 Rinse well with water. Allow surfaces to dry before allowing traffic or sealing.

MANUAL APPLICATION: WALLS



1 Dilute solution 1:1 with warm water and fill a light pressure sprayer.



2 Wet the surface with the solution and leave for 10-15 minutes. Work in manageable areas at a time.



3 Add a little water and gently scrub surfaces with a black pad to release any loosened matter from the surface.



4 Sponge to extract released residues from the surface. Repeat steps 2, 3 and 4 until the surface is clean.



5 Rinse well to finish. Allow to dry before sealing.

FURTHER INFORMATION

EQUIPMENT REQUIRED: Rotary scrubbing machine with onboard water tank, micro-fibre cloths, black or white emulsifying pad, buckets, sponges, absorbant towels (for spillage control), Plastic film and masking tape for covering and protecting any surfaces not to be cleaned.

Ensure that any sensitive surfaces not to be cleaned are properly covered and protected before beginning. Ensure that gloves, eye protection and suitable water proof clothing are worn at all times. Spillages of un-diluted cleaner should be wiped up and rinsed several times immediately.

After applying the cleaning solution to larger floor areas work in teams of two. One operator should agitate the surface using a rotary machine. The other

operator should use the wet vac or a sponge and water for immediate extraction. This will prevent released dirty residues from re-absorbing into the surface and greatly reduce the drying time of surfaces. Use cool water only within the tank on the scrubbing machine. Do not put intensive cleaning solution through the machine as this will impair its effectiveness. make sure underfloor heating is switched off and the surface of the tile is cool.

If applying to walls, steps or risers start on the top and work down. Try to work in manageable areas at a time and make sure to rinse well with plenty of water after each application. Rinsing should be repeated at least 2 times after cleaning. In areas where the staining is deep repeat the process until all of the stains have gone.