

Porcelain Tile Protector



A natural finish water based impregnating sealer that dries without altering the appearance. Helps protect against staining. Treated surfaces strongly repel water, oil, grease cements and resins. This product allows surfaces to breathe. Ideal for protecting pre and post grouting. This product is non film forming.

Coverage

	1 LTR	5 LTR	25 LTR
Low porosity surfaces	30 M ² /coat	150 M ² /coat	N/A

Technical Features

- Non hazardous
- High performance
- Low odour VOC free
- Invisible protection
- Easy to apply
- Breathable
- Interior & exterior
- Quick drying
- UV Resistant



Directions for use




1 Ensure surface to be treated is clean and as dry as possible before pouring the sealer onto the surface.




2 Spread out evenly using a sealant applicator pad, broad paint brush or foam roller. Repeat after 30 minutes. Leave to dry for 1 hour.



3 Grout in the joints or brush in jointing compound and clean off residues. Always follow manufacturers instructions.



4 When dry and free of residues apply a final coat of protector making sure to cover the joints as well.



5 Traffic can be allowed a few hours after application. Do not wash, cover or make excessively wet for at least 24hrs following treatment.

FURTHER INFORMATION

Ensure that any surfaces not to be treated are properly covered and protected before beginning. Ensure that gloves and eye protection are worn at all times. Some areas may look patchy following application, especially if the product is applied to surfaces that are still slightly damp. This is caused by retained moisture. This is normal. The impregnating sealer is breathable, so any damp patches caused by retained moisture should still dry to leave surfaces with an even appearance. This can sometimes take a further couple of days following application. Do not cover newly sealed surfaces with non-breathable membrane, cardboard, plastic sheets.