

Resin Residue Remover



A powerful non caustic stripper that softens most types of polymer, paint spots, silicone and epoxy residues for easy removal. Suitable for stone, travertine, sandstone, slate, marble, porcelain, ceramic, granite, terracotta, terrazzo, quarry, brick, concrete and masonry.

Coverage

	1 LTR	5 LTR	25 LTR
Mild cases	10 M ² /bottle	50 M ² /bottle	N/A
Severe cases	5 M ² /bottle	25 M ² /bottle	N/A
Extreme cases	3 M ² /bottle	15 M ² /bottle	N/A

Technical Features

- High performance
- Targets heavy or light films
- Walls & floors
- Rapid action
- Easy to use
- Interior & exterior
- Non drip




Directions for use

MANUAL APPLICATION REMOVING RESIDUAL POLYMER: FLOORS



1 Apply solution directly onto the surface. Do not dilute.




2 Brush out thickly and evenly and leave on the surface for a minimum of 30 minutes. Do not allow to dry. Add more to keep wet.



3 Scrub using a short haired stiff bristled brush. Rub surface with a clean lint free dry cloth to remove the softened films.



4 Rinse immediately with a sponge and water. Change rinsing water after every 5M².



5 Allow surfaces to dry. If small amounts of residue still remain repeat the process.

Directions for use (Cont.)

REMOVING PAINT SPOTS, EPOXY AND SILICONE RESIDUES: FLOORS



Apply directly to the surface from the container. Do not dilute.




Spread out evenly using a paint brush and leave for 30-40 minutes.



Scrub the surface to release any residues. Machines can be used.



Sponge up or extract released residues and rinse with water.



Allow surfaces to dry before allowing traffic.

FURTHER INFORMATION

USEFUL EQUIPMENT: Micro-fibre cloths, black or white emulsifying pad, buckets, sponges, absorbant towels (for spillage control), Plastic film and masking tape for covering and protecting any surfaces not to be cleaned.

Ensure that any sensitive surfaces not to be cleaned are properly covered and protected before beginning. Ensure that gloves, eye protection and suitable water proof clothing are worn at all times.

After applying the cleaning solution check after 15 minutes to make sure it is not drying out. If it appears to be drying then apply a little more solution. If a stiff scrubbing brush is not available then a mildy abraive emulsifying pad or microfibre cloth can be used to gently agitate the stain from the surface.