

SECTION 1: IDENTIFICATION OF THE PRODUCT

Product name: Pavestone Limestone Products

**Pavestone UK Limited,
Westington Quarry,
Chipping Campden,
Gloucestershire GL55 6EG.**

Tel: +44 (0) 1386 848650

Fax: +44 (0) 1386 849072

Email: enquiries@pavestone.co.uk

www.pavestone.co.uk

SECTION 2: HAZARDS IDENTIFICATION

Cutting lime paving can create dust, if inhaled in excessive quantities over extended periods. Respirable dust can constitute a long-term hazard.

Cutting lime Paving, unless adequately controlled, can project particles at high velocity, with consequent risk of impact damage and/or injury, particularly to exposed areas of the body and eyes.

Lifting and manual handling of large quantities can cause injury, and should be handled accordingly.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Natural Aggregated are produced from naturally occurring rock, sand and gravel deposits and consist of combinations of various minerals including quartz. The cement admixture has irritant properties prior to curing.

SECTION 4: FIRST AID MEASURES

First Aid treatment is as follows:

Eye Contact

Immediately rinse under running water and consider medical attention.

Cuts/Abrasions

Cuts/Abrasions from handling should be cleaned and treated, using the normal first-aid method. Wounds must receive prompt medical attention.

In all doubtful cases, medical advice must be obtained.

SECTION 5: FIREFIGHTING MEASURES

Not Applicable.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Avoid contact with Skin

Take up product using appropriate equipment.

SECTION 7: HANDLING AND STORAGE

Avoid contact with dust.

Always follow safe lifting and manual handling procedures.

The preferred method of handling is by mechanical means. Where storage of material is necessary in public areas accessed by the public, adequate notices, signs and markings should be used.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Although not classed as dangerous these products should be handled in accordance with good industrial hygiene and safety practices. Whilst handling products, protective gloves and boots should be worn.

During cutting or similar activity, overalls/eye/face protection should be worn, use dust masks. Respiratory protective equipment to BS 2901 Type B with extraction equipment.

8.1 Hand Protection

Wear suitable protective gloves.

8.2 Skin Protection

Avoid contact with skin.

8.3. Eye Protection

Wear goggles to protect eye contact from flying particles when crushing, drilling, cutting or breaking paving.

8.4 Masks

Wear dust masks when crushing, drilling, cutting or breaking paving.

8.5 Footwear

Wear footwear with protective toecaps when working with the products.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

The paving can be abrasive and the dust contains calcium silicates.

SECTION 10: STABILITY AND REACTIVITY

Not applicable.

SECTION 11: TOXICOLOGICAL INFORMATION

No risk upon observation of safety instructions 6, 7 & 8 above.

SECTION 12: ECOLOGICAL INFORMATION

Have no ecological effect.

SECTION 13: DISPOSAL CONSIDERATIONS

Limestone paving may be recycled or placed in an approved landfill.

SECTION 14: TRANSPORT INFORMATION

Ensure security and safety of load at all times.

SECTION 15: REGULATORY INFORMATION

Not Applicable

SECTION 16: OTHER INFORMATION

The information contained in this sheet is correct to the best of our knowledge at the date of issue. It is intended as a guide of safety requirements only and it is not a specification or guarantee of specific properties.

We recommend customers ensure that the product is entirely suitable for their purposes.

No liability can be accepted for any loss, injury or legal requirements and local regulations.