

Exterior use

Water based Impregnating Sealer.

For all types of natural and reconstituted stone paving, Suitable for smooth (honed/polished) and rougher (sawn, split and textured) surfaces. Provides an enhanced natural finish. Helps protect against staining. Strongly repels water, oil and grease. Allows surface to breathe. Helps reduce efflorescence.

Directions for use

Always test on an inconspicuous area prior to general application.

Preparation: Ensure surface to be treated is completely clean, dry and free from dirt, grime, cement and grout. First wash surfaces with a dilute solution of **Pavestone Patio Cleaner** 1:10. Rinse well to remove residues and leave to dry (24hrs).

Application: SHAKE WELL BEFORE USE

Apply generously and evenly using a light pressure sprayer, foam roller or paint brush. On more absorbent surfaces apply further coats at hourly intervals until the surface is fully saturated.

On higher porosity materials sufficient sealer should be applied until treated surfaces are fully saturated.

Any dried on and over applied sealer can be removed by rubbing with damp micro fibre cloth, or on larger areas with a rotary machine with brushes. If dried on residues are left too long and are difficult to buff away; apply a little soapy water and gently scrub with a scrubbing brush. Rinse and leave to dry.

Do not use in temperatures under 5°C or over 25°C.

Storage information

KEEP UPRIGHT in a cool, dry, frost free environment.

Shelf life: Up to 2 years for un-opened containers. Once opened use within 6 months of purchase for optimum results.

Empty containers are recyclable. Active ingredients are water soluble and inert once cured so therefore not harmful to the environment and ecologically sound.

Coverage M² per coat

	1 LTR	5 LTR
Honed surfaces	30m ²	150m ²
Medium porosity surfaces	15m ²	75m ²
High porosity surfaces	7.5m ²	37.5m ²

Health, Safety & Environmental

Keep out of reach of children.

Dispose of contents/container to a licensed waste centre in accordance with local /regional/national/international regulations.



This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area.